

PRO Series Specification


DF7SWW

24V-10mm





【General description】

- Linear two-color light bar without light spot, large light-emitting angle
- High quality FPC, high thermal conductivity 3M glue
- Easy to install and maintain
- Ta: -25~40°C; Tc: 75°C(max)



【Dimension】

- | | |
|-----------------------------------|--|
| Input voltage: DC24V | Max.length: 5000mm(16.4') |
| CRI: >90 | Cutting unit: 27.78mm(1.09") |
| Max.power: 9.6W(1m) | LED pitch: / |
| Power range: 7.9~9.6W(1m) | Min. bend diameter: Φ 60mm(2.36") |
| Rated current: 0.37A(1m) 1.6A(5m) | Mounting: 3M tape |
| Typical Power: 8.8W(1m) 38.5W(5m) | Copper foil: 2oz |
| IP: IP20/IP65/IP67 | |
| On-off times: 10000 (test times) | |
| Warranty: 3years | |
| (Warranty based on indoor age) | |





【Photo-electric Parameters】





CRI	Color	CCT	Lumen(lm/m)	Lumen(lm/ft)	lm/W	ErP 2019
Ra>90	SW	2700K	350	106	81	G
Ra>90	W	6000K	380	115	88	G
Ra>90	SWW	2700K+6000K	720	219	84	G

- 1.The tolerance of output data can be vary up to 15%.
- 2.the output data tested according to IES TM-30-15.
- 3.the output data is based on IP20/lmerter, data of 5m in only for reference.
- 4.IP protection process leads changes to size, CCT and luminous flux.






【IP process information】



【Electronic & output data】


IP Process	Picture	Picture description	Size	optional CCT/color for finished product	lumen output rate
NO		No proof	10mm*1.6mm	2700K+6000K	100%
NA		Nano-proof	10mm*1.6mm	2700K+6000K	98%
ET		Extrusion tube	12mm*4.8mm	2700K+6000K	88%
EG		Extrusion curved tube	11.3mm*3.8mm	2700K+6000K	80%

【Accessories Information】


Name	Picture	Code	coding	description
Fixed Clip		94-02-00-0003	FSW10SA	Silicone clip, screw: PA 3*8mm, suitable for 10mm FPC,EF/ET strip
Silicone Plug Kit		94-02-00-0046	DT10EA-A	Silicone plug kit is suitable for 10mm board width, ET/EF series silicone extrusion light strip
Silicone stopper kit		94-02-00-0047	DW10EA-A	Silicone tail plug kit is suitable for 10mm board width, ET/EF series silicone extrusion light strip
Mounting groove		94-02-00-0025	CVT10EA-14100100	Transparent PVC mounting groove,suitable for 10mm FPC,silicone extruded EF/ET strip
Stopper glue		94-16-03010001	AS-PG-0003	Silicone gel,suitable for ET/EF/EG waterproof LED strip

【Packing】

Colors brand package(NONA)



General customized package(ET)



IP Process	Product size(mm)	Product quantity (m/reel)	Product quantity (m/case)	Product net weight(kg)	Net weight per box(kg)	Gross weight(kg)	Package size (cm)
NO	5000*10*1.6	5	270	0.12	6.48	7.42	36.5*36.5*19
NA	5000*10*1.6	5	270	0.13	7.02	8.1	41*41*26
EG	5000*11.3*3.8	5	200	0.36	14.4	15.48	41*41*26
ET	5000*12*4.8	5	200	0.4	16	17.08	41*41*26

Remark: data with 10% tolerance

【Precautions】

- Please drive the led strip with 24VDC isolated power, and the ripple of the constant voltage source should be less than 5%.
- Please do not bend the strip into an arc with a diameter less than 60mm to ensure the longevity and reliability.
- Do not fold it in case any damage of LED beads.
- Do not pull the power wire hard to ensure the longevity. Any Crash may damage the LED light is prohibited.
- Please make sure the wire is connected to the anode and cathode correctly. The power output should be consistent with the voltage of the strip to avoid damage.
- LED lights should be stored in dry, sealed environment. Please only unpack it before usage. Ambient temperature: -25℃~40℃. Storage temperature: 0℃~60℃. Please use the strips without waterproof within indoor environment with humidity less than 70%.
- Please be careful during operation. Do not touch the AC power supply in case of electric shock.
- Please leave at least 20% power for the power supply during using to ensure there is enough power supply to drive the product.
- Do not use any acid or alkaline adhesives to fix the product (e.g.: glass cement).
- Do not scratch the product when IP process of the product is NA. Ultraviolet rays will damage the nano-layers on the product and seriously affect the life of the product.