



- Recommended for the construction of sealed lighting fixtures

**APPLICATION**

- LED protection and light diffusion in lighting fixtures

**MOUNTING**

- to the profile, by pressing

**ADDITIONAL INFORMATION**

- standard lengths of KLUŚ profiles and covers: 1000 mm (tolerance ± 1.5 mm) and 2005 mm / 3010 mm (tolerance + 5 mm); for selected covers: 6050 mm, 10050 mm (tolerance + 5 mm)
- when choosing a different length of profiles / covers than available in the standard, you should additionally choose the cutting service at KLUŚ

**TECHNICAL DRAWING**



**TECHNICAL SPECIFICATIONS**

Material	PC
Shape	flat
Maximum length on request	3000 mm
Width	12.5 mm
UV resistance	yes


Color	Length	Light transmission	Possibility of obtaining a line of light	Ref
<input type="checkbox"/> frosted	1000 mm	73 %	yes	B17208M_1 1369_1
	2005 mm			B17208M_2 1369_2
	3010 mm			B17208M_3 1369_3
<input checked="" type="checkbox"/> clear	1000 mm	94 %	no	B17208T_1 1370_1
	2005 mm			B17208T_2 1370_2
	3010 mm			B17208T_3 1370_3

# Cover HS


Ref. B17208M, B17208T

Ref. arch 1369, 1370

## RELATED PROFILES



**PDS-MDF**  
0971\_1



**STOS-MDF**  
0974\_1

## RELATED PROFILES > ARCHITECTURAL



**KOZMA**  
A18040  
Ref. arch 18040




**OPK-4**  
A00370  
Ref. arch C0370



**PDS-T**  
A02057  
Ref. arch C2057



**PDS-UST**  
A02725  
Ref. arch C2725




**POK-US**  
A01234  
Ref. arch H1234




**POKET**  
A01179  
Ref. arch H1179


## RELATED PROFILES > FOR MAIN LIGHTING



**DES**  
A18030  
Ref. arch 18030



**MOD-100**  
A18049A  
Ref. arch 18049




**MOD-50**  
A18047  
Ref. arch 18047

## RELATED PROFILES > FOR SCONCES AND WALL LIGHTING


# Cover HS

Ref. B17208M, B17208T


Ref. arch 1369, 1370



**LIT-L**  
A18033  
Ref. arch 18033




**OBIT**  
A04826  
Ref. arch W4826




**PLAKIN-DUO**  
A04106

## RELATED PROFILES > ILLUMINATION OF COVES AND ARCHITECTURAL NICHES



**NISA-KON**  
A18027  
Ref. arch 18027



**NISA-KRA**  
A18026  
Ref. arch 18026



**NISA-NI**  
A18029  
Ref. arch 18029




**POLI**  
A07176  
Ref. arch B7176

## RELATED PROFILES > STAIRS ILLUMINATION



**POR**  
A06144  
Ref. arch B6144



**STEP**  
A18042  
Ref. arch 18042

## RELATED PROFILES > TRANSPARENT PANEL ILLUMINATION



**PULA**  
A18035  
Ref. arch 18035

# Cover HS

Ref. B17208M, B17208T

Ref. arch 1369, 1370


## RELATED PROFILES > UNIVERSAL



**45-16**  
A08504  
Ref. arch B8504



**45-ALU**  
A04023  
Ref. arch B4023




**KUBIK-45**  
A07697  
Ref. arch B7697



**MICRO-ALU**  
A01888  
Ref. arch B1888



**MICRO-H**  
A00599  
Ref. arch C0599



**MICRO-HG**  
A01419  
Ref. arch C1419



**MICRO-NK**  
A01587  
Ref. arch C1587



**MICRO-PLUS**  
A02966  
Ref. arch C2966



**OLEK**  
A08505  
Ref. arch B8505



**PDS-4-PLUS**  
A01263  
Ref. arch C1263



**PDS-H**  
A0920  
Ref. arch B9204



**PDS-NK**  
A01588  
Ref. arch C1588




**PDS-ZM-PLUS**  
A02056  
Ref. arch C2056



**PDS-ZMG**  
A01418  
Ref. arch C1418

## RELATED SYSTEMS > GENERAL LIGHTING SYSTEMS



**MOD-50**  
18047



**PK-4**  
A18044+A00370  
Ref. arch 18044+C0370